

# TECHNICAL DATASHEET

# 5X3033300

Rev.00

U+DC



## FEATURES:

- Exclusive UDC coating
- Lens with FLD (Floating Lens Design) technology
- Frame engineered to cushion the contact points on the face
- Extended 9 base wraparound lens, provides extra coverage around the eyes
- Ventilation system
- The spectacle fits the face without adjustments

## FRAME FEATURES:

Frame Typology	<b>Spectacle</b>
PPE field of view	<b>&gt;40°</b>
Temple adjustment	-
Weight (g)	<b>31</b>
Size (mm)	<b>142 122</b>
Material Features	<b>Anallergic</b>

## FEATURES OCULARS/LENSES:

Ocular/Flip-up Material	<b>Polycarbonate</b>
Colour	<b>Clear</b>
Technical Treatment	<b>U+DC</b>
Aesthetic Treatment	-
Thickness [mm](+/- 0.1)	<b>2.2</b>
Curvature	<b>Base 9 Spheric</b>
Optical Class	<b>1</b>
UV Protection	<b>380 nm</b>
Spare parts	-
VLT% (+/-5%)	<b>91,2</b>

## MARKING DATA:

Standard References	<b>EN166 EN170</b>
Frame Marking	<b>Mod.5X3 U EN166 FT CE U EN 175 FT CE</b>
Ocular/Flip-up Marking	<b>2C-1.2 U 1 FT K N CE</b>

## APPLICATION FIELDS

Protection against high-speed particles 45 m/s - low energy (F); Protection against high-speed particles at extreme temperatures (T); Resistance to fogging of oculars (N); Resistance to surface damage by fine particles (K)

Notes

