

Safety / Spectacles / 5X9 SPORT

5X9 SPORT - Solar Polarized

Code: 5X9.03.02.P2

Date: 16-03-22 1/2

Safety glasses enter a new dimension, designed to have the maximum impact protection and guarantee comfort and lightness as sport glasses.



Frame mark (EU)

U EN166 FT CE

Lens mark (EU)

2C-3/5-3.1 U 1 FT K N CE

Conditions of use

High brightness, Light reflections

Lens color

Grey

Frame technology

Adjustment of temples in length, Adjustment of temples in inclination, Rubber Terminal, Terminal tilting movement, SoftPad

Lens technology

Anti-Scratch + Anti-Fog (KN - Vanguard PLUS), Polarized (Polar-X)

Lens material

Polycarbonate

Standards

EN166, EN170, EN172

Scale number

(2C-3), (5-3.1)

Mechanical resistance

Low energy impact (F)

Optical class

Optical class (1)

Optional requirements

Resistance to surface damage by fine particles (K), Resistance to fogging of oculars (N), Protection against high speed particles at extreme temperatures -5°/+55° C (T)

Weight

35g

>> <https://www.univetsafety.com/en/products/safety/spectacles/5x9-sport/5x9-sport-solar-polarized/>



01.

SIDE SHIELD WITH VENTILATION SYSTEM

Increases the level of peripheral protection while reducing the risk of fogging, thanks to a ventilation vent

02.

INCLINATION ADJUSTMENT

Allows to adjust the height of the glasses to ensure maximum optical quality

03.

RUBBER TERMINAL WITH TILTING MOVEMENT

Allows the glasses to adhere to the temples for a perfect grip

04.

LENGTH ADJUSTMENT

Allows to obtain the correct fit and work in constant safety

Attention! Any images on this page illustrate the frame technologies of the product family in question and may represent frame and lens colours that do not correspond to the product code of the following sheet.

HEADQUARTERS

Univet S.r.l. Via Giovanni Prati 87 25086 Rezzato - Telephone 030 2499411 - Fax 030 2499430 - info@univetsafety.com
VAT. IT02506570163