

FA 60 0006 10/20:

PVC +  STEEL

FA 60 006 10S/20S:

PVC +  INOX

## HS CODE

76169990

## CARTON SIZE / PCS.

**FA 60 006 10/S** : 40 x 40 x 24 cm / 25**FA 60 006 20/S** : 40 x 40 x 24 cm / 20





FA 60 006 XX: AET (UE) N°2777/11681-01/E00-00

FA 60 006 XXS: AET (UE) N°2777/10792-02/E01-01

**Satra Technology Europe Ltd., N° 2777,**  
 Bracetown Business Park, Clonee,  
 Dublin, D15YN2P, Ireland

## MODULE D FI14/14003.02

**SGS Fimko Oy, N°0598**
 Takomotie 8,  
 00380 HELSINKI, Finland

REF.	FA 60 006 10   FA 60 006 20   FA 60 006 10S   FA 60 006 20S
CE	EN 795:2012 Type B
	x1
LG.	1.0 m   2.0 m   1.0 m   2.0 m
MAT.	PVC /  STEEL Ø 8.0 mm   PVC /  INOX Ø 8.0 mm
R (kN) / MBS (kN)	12 kN / 25 kN
	0.56 kg   0.80 kg   0.46 kg   0.74 kg



**Nombre d'utilisateurs**  
 Number of users  
**Cantidad de usuarios**  
 Quantità di utilizzatori  
**Anzahl der Benutzer**

**R (kN) / MBS (kN)**

**Résistance statique (en kN) / Résistance à la rupture**  
 Static strength / Minimum Breaking Strength  
**Resistencia estática (en kN) / Resistencia a la ruptura (en kN)**  
 Resistenza statica (in kN) / Resistenza alla rottura (in kN)  
**Statische Festigkeit (in kN) / Bruchfestigkeit (in kN)**